

SOFTY

thickness: 1.2-1.4MM
average size: 50 sq. ft
availability: In Stock
category: Protected
finish type: Soft Pebble Grain
raw material: South American
Made in Italy

Softy is one of our most aggressively priced leathers. It's aniline dyed and has a protective finish topped off with a grain assist to give Softy a consistent even pebble grain and color. Its suppleness is perfect for residential use yet it's unique and durable finish will pass the strictest commercial code.

Colorways available: Antique, Bark, Black, Chestnut, Granite, Henna, Ivory, Java, Khaki, Light Grey, Navy and Red

SPECIFICATIONS

performance characteristics

PERFORMANCE LEATHER

EN ISO 4045 DETERMINE Ph & Ph (DIFFERENCE FIGURE)	Min 3,2
ISO105/B02	Grey Scale ≥ 3 on specimen
COLOR FASTNESS OF LEATHER TO LIGHT: XENON LAMP	Grey Scale = 3 on Reference Blue Wool #5
EN ISO 15700 COLOR FASTNESS TO WATER SPOTTING	Grey Scale ≥ 3 (No permanent swelling)
ISO 11641 COLOR FASTNESS OF LEATHER TO PERSPIRATION	80 Cycles ≥ 3.5
EN ISO 11640 COLOR FASTNESS OF LEATHER TO RUBBING	500 Cycles Dry ≥ 4 250 Cycles Wet ≥ 3.5
EN ISO 11644 FINISH ADHESION	3 N/cm
EN ISO 3376 MEASURE TENSILE STRENGTH AND % ELONGATION	Tensile Strength ≥ 8 Mpa % Elongation $\leq 80\%$
EN ISO 5402 FLEXING ENDURANCE (FLEXOMETER METHOD)	50,000 Cycles (no finish damage cracks)
EN ISO 17233 COLD CRACK RESISTANCE OF FINISH	-15°C (no finish cracks)
EN ISO 3377-1 TEAR STRENGTH (SINGLE EDGE TEAR)	>20 N Minimum

flame resistance

CA TB 117 - 2013	Complies
NFPA - 260 CIGARETTE IGNITION	Class 1
FMVSS 302	Complies

